

► PRINTER MODEL

LM-550A2/PC

*Standard model



**PORTABLE PRINTER FOR
CONTROL PANEL
WIRE NUMBERING &
DEVICE LABELING**

► SPECIFICATIONS

ITEMS	CONTENTS
Name	ELECTRONIC LETTERING MACHINE LM-550A2/PC
Dimensions	295 (W)×293 (D)×94 (H) mm
Weight	2.3kg
Printing method	Thermal transfer method (300dpi)
Display	LCD dot matrix : 64×160 Pixel (Backlit)
Printing speed	40mm/s (Standard) 20mm/s (Low temperature mode)
Maximum Printing length	Tube : 100m, Tape : 5m By multiple copy printing, maximum 30copies, upto Tube ; 100m, Tape ; 7m
Maximum number of characters to input	5,000 characters per file
Character size	1.3, 2, 3, 4, 6mm height
Usable tube	φ1.5mm ~ 8.0mm (Vinyl Tubing) [For GRIP TUBE, φ1.5~2.0mm tubes, the dedicated attachment (standard accessory) is required.] φ2.0mm ~ 6.5mm (Heat Shrink Tubing)
Usable tape	Width 5, 9, 12mm (Max genuine tape)
Usable ID Plate	2.5/4.1/4.6/6.3/9.0mm wide. *ID Plate Attachment Only compatible with MAX brand 4.1mm wide.
Tube cutting method	Auto half cut, manual full cut
Internal memory	250,000 characters (Maximum 50 files)
External memory	USB memory
Interface	USB 2.0 full speed
Power supply	DC12V, 3.0A Use only specified AC Adapter (100V~240V) included in the package
Power consumption	Max 36W
Operating environment	10°C to 35°C

► CONSUMABLES & OTHER ITEMS

INK RIBBON CASE	20PCS./CTN	*L Tube (Vynyl(PVC)/Drum roll)
LM-RC500		*Not UL certified
ECONOMICAL INK RIBBON REFILLS		
	10 ROLLS/BOX	
LM-IR50B (BLACK)	110m/ROLL	LM-TU425L2 WHITE φ2.5mm x 250m / ROLL
		LM-TU432L2 WHITE φ3.2mm x 250m / ROLL
		LM-TU436L WHITE φ3.6mm x 200m / ROLL
		LM-TU442L WHITE φ4.2mm x 200m / ROLL
		LM-TU452L WHITE φ5.2mm x 135m / ROLL
INK RIBBON REFILLS FOR HEAT SHRINK TUBING		
	10 ROLLS/BOX	
LM-IR50BP (BLACK)	110m/ROLL	LM-TU464L WHITE φ6.4mm x 100m / ROLL
LM-IR50W (WHITE)	70m/ROLL	LM-TU480L WHITE φ8.0mm x 70m / ROLL

HALF CUTTER *REPLACEABLE

LM-HC340	2pcs/box
-----------------	----------

POLYESTER TAPE CASSETTE 10PCS./BOX

LM-TP505W (WHITE)	5mm(W) × 16m(L)/PC
LM-TP505Y (YELLOW)	5mm(W) × 8m(L)/PC
LM-TP505T (TRANSPARENT)	5mm(W) × 8m(L)/PC
LM-TP509W (WHITE)	9mm(W) × 16m(L)/PC
LM-TP509Y (YELLOW)	9mm(W) × 8m(L)/PC
LM-TP509T (TRANSPARENT)	9mm(W) × 8m(L)/PC
LM-TP512W (WHITE)	12mm(W) × 16m(L)/PC
LM-TP512Y (YELLOW)	12mm(W) × 8m(L)/PC

UBON PVC White Tube

UT-N2.5W White--	> Dia.2.5mm.x200m./Roll
UT-N3.2W White--	> Dia.3.2mm.x200m./Roll
UT-N3.6W White--	> Dia.3.6mm.x200m./Roll
UT-N4.2W White--	> Dia.4.2mm.x200m./Roll
UT-N5.2W White--	> Dia.5.2mm.x100m./Roll
UT-N6.0W White--	> Dia.6.0mm.x100m./Roll

PC REQUIREMENTS For Windows 10 / 8.1 / 8 / 7 operating systems. Windows® is a registered trademark of Microsoft Corporation(US) in U.S.A. or other countries.

*The specifications and design of products in this catalog will be subject to change without advance notice of our products due to our continuous efforts to improve quality.